

ARC-10W39

**10.1" Intel® Processor N97/ X7433RE /N150
Fanless Rugged Touch Panel PC with IET
Expansion**



Product Features

- Full flat front panel with projected capacitive touch supports multi touch
- Intel® Processor N97/ X7433RE /N150 (Option Core i3-N305/ i3-N355)
- 2 x LAN (2.5GbE), 2 x COM, 2 x USB3.2
- Available expansion for audio, USB, COM, HDMI, MPCIe, GPIO, CAN bus
- Wi-Fi / BT / 4G / 5G (by option)
- Fanless operation
- Service window for storage and memory module
- TPM2.0
- 10.1" WXGA LCD with PCAP multi-touch
- 1 x 262-pin DDR5 4800MHz SO-DIMM socket, supports up to 16GB max (non ECC only)
- 1 x USB type C (w/ PD(20V/3A input), USB3.2(Gen2x1, 10Gbps, 5V/3A output), display function)
- 2 x M.2 slots (Key-B 2242/3042/3052 with SIM slot1, Key-E 2230)
- Rugged design for vibration & shock protection
- Wide range DC power input +12 ~ 24Vdc
- IP65 compliant front panel, IP41 rear box

Specification

System Information

Processor	Intel® Alder Lake-N N97, 6M Cache, up to 3.6 GHz, 12W Intel® Amston Lake X7433RE, 6M Cache, up to 3.40 GHz, 9W Intel® Twin Lake N150, 6M Cache, 0.8 GHz up to 3.60 GHz, 6W
System Memory	262-pin DDR5 4800MHz SO-DIMM socket, supports up to 16GB max (non ECC only)
Watchdog Timer	H/W reset, 1sec. ~ 65535sec
H/W Status Monitor	CPU & system temperature monitoring and voltages monitoring
TPM	TPM 2.0 (by default)
SBC	ARC-ASL
CPU Cooler (Type)	Fanless heatsink

Expansion

Expansion	1 x M.2 (Key-B, 2242/3042/3052, SATAIII, USB3.2 Gen1x1(default, 5Gbp/s)) or PCIe1(via OEM BIOS request), USB2.0, SIM slot for LTE cards (*not support PCIe2 device) 1 x M.2 (Key-E, 2230, PCIe1, USB2.0) 1 x 80-pin IET interface
-----------	--

Storage

Storage	1 x 2.5" Drive bay(7mm HDD restricted)
HDD/ SSD	1 x SATA3
Other Storage Device	1 x M.2 Key-B 2242/3042/3052 for M.2 SATAIII SSD

Audio

Audio Codec	Realtek ALC888S
Speaker Output	2 x 2W

Ethernet

LAN Chipset	2 x Intel® I226IT 2.5 Gigabit Ethernet
Ethernet Interface	10/100/1000/2.5G Base-Tx GbE compatible

Power Requirement

DC Input	+12V ~ +24V
DC Input Connector	Lockable DC Jack (default) Optional for phoenix connector
ACPI	Single power ATX support S0, S3, S4, S5 and ACPI 3.0 compliant

Software Support

OS	Win10 / Win11 / Linux
----	-----------------------

Certification

Certification Information	CE / FCC Class A / VCCI
---------------------------	-------------------------

Panel

LCD Size	10.1", 16:10
Display Type	WXGA
Resolution	1280 x 800
Pixel pitch	0.1695mm(H) x 0.1695mm(V)

Luminance	400 cd/m2
Contrast ratio	800
Viewing angle	85 (U), 85 (D), 85 (L), 85 (R)
Response time	25 ms
Backlight	LED
Touch Type	Projective capacitive multi-touch up to 10 points
Touch Light Transmission	88%
Touch Controller	EETI

External I/O

USB Port	2 x USB3.2 (1 x double deck, type A) 1 X USB type C (w/ PD(20V/3A input), USB3.2(Gen2x1, 10Gbps, 5V/3A output), display function)
LAN Port	2 x RJ-45
COM Port	1 x RS-232/422/485 1 x RS-232

Internal I/O

Expansion	1 x M.2 (Key-B, 2242/3042/3052, SATAIII, USB3.2 Gen1x1(default, 5Gbp/s)) or PCIe1x1(via OEM BIOS request), USB2.0, SIM slot for LTE cards (*Not support PCIe2 device) 1 x M.2 (Key-E, 2230, PCIe1, USB2.0) 1 x 80-pin IET interface
DIO	12-bit GPIO + 2-pin CAN bus (by ARC-BYT DB-E)
Other	3 x Knockouts for antenna mounting

System Control

LED Indicator	HDD LED, power LED
---------------	--------------------

Mechanical & Environmental

Operating Temp.	-10°C ~ 50°C (-14°F ~ 122°F)
Storage Temp.	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	40°C @ 95% Relative humidity, non-condensing
Dimension (W x L x H)	282.4 x 201 x 50.9mm
Weight	2.3 Kg
Vibration Test	With SSD/mSATA : 2.24Grms, IEC 60068-2-64, random, 5 ~ 500Hz, 1hr/axis

Shock Test	Operating with SSD/CFast/mSATA : MIL-STD-810G, method 516.6, procedure I, functional shock=20G
Drop Test	ISTA 2A, IEC-60068-2-32 Test:Ed
IP Rating	Front panel IP65 Back cover IP41
Mounting Kit	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm
Power Mode	AT/ATX (ATX is default)
System Fan	Fanless
Construction - Front	Die casting with cover lens
Construction - Rear	Black die casting

Component

Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 72W adapter (19V @ 3.78A adapter) AC-DC adapter
----------------	---

Ordering Information

ARC-10W39-150-B1R

10.1" 1280x800 400nits Industrial Touch Panel PC, ErP Design,
PCAP Multi TouchIntel Processor N150 0.8 GHz up to 3.60 GHz CPU/2GLAN/2COM/2USB3/USB
typeC/SPK/12~24V input/72W Adapter

ARC-10W39-355-B1R

10.1" 1280x800 400nits Industrial Touch Panel PC, ErP Design, PCAP Multi Touch

Intel Processor i3-N355, 3.90 GHz CPU/2GLAN/2COM/2USB3/USB typeC/SPK/12~24V
input/72W Adapter

ACC-ARC-USB-1R

4 x USB 3.0 Kit for ARC Series

ACC-ARC-AUDIO-1R

HDMI + 5.1 CH Audio Kit for ARC Series

ACC-ARC-MPCIE-1R

HDMI + MPCIE w/SIM Kit for ARC Series

ACC-ARC-COM-1R

2 x Isolated RS-232 Kit for ARC Series

ACC-ARC-COM-2R

3 x RS-232 Kit for ARC Series

ACC-ARC-COM-3R

2 x RS-232 + USB Kit for ARC Series

ACC-ARC-COM-4R

2 x RS-232 + LAN Kit for ARC Series

ACC-ARC-GPIO-1R

12-bit GPIO + 2-pin CAN Bus Kit for ARC Series

ACC-ARC-OBDII-1R

OBDII - CAN Bus Kit for ARC Series (OBDII/EOBD for Small Vehicle)

ACC-ARC-OBDII-2R

OBDII - CAN Bus Kit for ARC Series (J1939J1708 for Large Vehicle)

ACC-ARC-OBDII-3R

OBDII - CAN Bus Kit for ARC Series (ISO15765-4 for Special Large Vehicle)

E1702031835R

USA Power Cord

E170203183DR

EU Power Cord

E170203183BR

Japan Power Cord

E170P060370R

UK Power Cord

E170P060392R

Australia Power Cord